

DEUTZ-FAHR AGROFARM 5095 GS

40 KM/H

97HP



THE ALL-ROUNDER UTILITY TRACTOR

Welcome to the world of the new Agrofarm 5-Series, an outstanding range of tractors that embody versatility, modularity, strength and an enviable good value for money ratio within the utility mid-segment.

The tractors in the Agrofarm 5-Series are designed to offer maximum flexibility while ensuring reliable and innovative performance. Agility is one of the distinctive features of these tractors, thanks to a remarkable steering angle and cutting-edge solutions such as the PowerShuttle with adjustable response, Stop & Go system, and Comfort Clutch, which ensure smooth and comfortable driving even in the most challenging situations.

ENGINE

- FARMotion LCR Diesel Engine
- 4 Cyl/3849cc Turbocharged Intercooled
- Liquid/Oil Cooled
- High-Pressure Diesel Injection/Common Rail
- Engine speed programming – 2 Settings
- 97Hp @ 2000 rpm (ECE R120)
- 5Hp Power Boost
- Torque 368 Nm @1600 rpm
- Powercore Air Filter with Dust Ejectors
- VISCO cooling fan
- Vertical exhaust pipe on cab
- 145 lt Fuel Capacity

TRANSMISSION

- 20/20 Forward/Reverse Gears
- Wet clutch Powershuttle
- Shuttle Modulation with 5 Settings
- 5 Speeds / 2 Ranges / 2 Stage Powershift
- Comfort Clutch
- Front Wheel Assist - Push Button
- 4 Wheel Independent Braking
- 100% Front & Rear Diff Lock - Push Button
- 40 km/h Road Speed
- Pre-Arrangement For Front End Loader

PTO

- Independent Wet Multidisc Clutch
- 2 Speed PTO 540/540E
- 540 PTO @ 1958 Rpm
- 540E PTO @ 1641 Rpm
- 1" 3/8 - 6 Spline PTO Shaft

WHEEL EQUIPMENT & MISCELLANEOUS

- Adjustable Radial Wheel Equipment
- 420/70R24 Front 480/70R34 Rear
- Rear Wheel Ballast 172 kg
- Front Dynamic Fenders

OPERATOR ENVIRONMENT

- 4 Post Air Conditioned Cab
- High visibility transparent roof FOPS-compliant (polycarbonate hatch) with sunshade grid
- HYDRO Silent-Block Cab Suspension
- Ergonomic Controls
- Multi Function Digital Dash
- Deluxe Air Seat
- Passenger seat with seatbelt
- MP3 Radio Player with Twin Speakers
- Cup and smartphone holder
- Telescopic Mirrors
- 4 Rear Work Lights
- 4 Upper Headlights
- Rotating Beacon

HYD/LINKAGE/DRAWBAR

- Open Centre Hydraulic System
- 56 L/min Hyd Pump
- Separate 35L/min Steering Pump
- 2 Sets of Remotes - Kickout/Float
- Mechanical Linkage c/w Position & Draft Controls
- Rear lift with External Control
- Cat 2 Hook Ends
- 3600kg Lift Capacity
- Swinging Drawbar - CAT A

WEIGHTS & DIMENSIONS

Wheelbase: **2400mm**

Length: **4268mm**

Total Height: **2494mm**

Total Weight: **4000kg**

DEALER DETAILS

DEUTZ-FAHR AGROFARM 5105 GS

40 KM/H

106HP



THE ALL-ROUNDER UTILITY TRACTOR.

Welcome to the world of the new Agrofarm 5-Series, an outstanding range of tractors that embody versatility, modularity, strength and an enviable good value for money ratio within the utility mid-segment.

The tractors in the Agrofarm 5-Series are designed to offer maximum flexibility while ensuring reliable and innovative performance. Agility is one of the distinctive features of these tractors, thanks to a remarkable steering angle and cutting-edge solutions such as the PowerShuttle with adjustable response, Stop & Go system, and Comfort Clutch, which ensure smooth and comfortable driving even in the most challenging situations.

ENGINE

- FARMotion LCR Diesel Engine
- 4 Cyl/3849cc Turbocharged Intercooled
- Liquid/Oil Cooled
- High-Pressure Diesel Injection/Common Rail
- Engine speed programming – 2 Settings
- 106Hp @ 2000 rpm (ECE R120)
- 5Hp Power Boost
- Torque 425 Nm @1600 rpm
- Powercore Air Filter with Dust Ejectors
- Vertical exhaust pipe on cab
- 145 lt Fuel Capacity

TRANSMISSION

- 40/40 Forward/Reverse Gears
- Wet clutch Powershuttle
- Shuttle Modulation with 5 Settings
- 5 Speeds / 4 Ranges / 2 Stage Powershift
- 0.3Km/h – 40 ECO Km/h
- Comfort Clutch
- Front Wheel Assist - Push Button
- 4 Wheel Independent Braking
- 100% Front & Rear Diff Lock - Push Button
- 40 km/h Road Speed
- Pre-Arrangement For Front End Loader

PTO

- Independent Wet Multidisc Clutch
- 2 Speed PTO 540/540E
- 540 PTO @ 1958 Rpm
- 540E PTO @1641 Rpm
- 1" 3/8 - 6 Spline PTO Shaft

WHEEL EQUIPMENT & MISCELLANEOUS

- Adjustable Radial Wheel Equipment
- 420/70R24 Front 480/70R34 Rear
- Rear Wheel Ballast 172 kg
- Front Dynamic Fenders

OPERATOR ENVIRONMENT

- 4 Post Air Conditioned Cab
- High visibility transparent roof FOPS-compliant (polycarbonate hatch) with sunshade grid
- HYDRO Silent-Block Cab Suspension
- Ergonomic Controls
- Multi Function Digital Dash
- Deluxe Air Seat
- Passenger seat with seatbelt
- MP3 Radio Player with Twin Speakers
- Cup and smartphone holder
- Telescopic Mirrors
- 4 Rear Work Lights
- 4 Upper Headlights
- Rotating Beacon

HYD/LINKAGE/DRAWBAR

- Open Centre Hydraulic System
- 56 L/min Hyd Pump
- Separate 35L/min Steering Pump
- 3 Sets of Remotes - Kick out, Detent/Float
- Mechanical Linkage c/w Position & Draft Controls
- Rear lift with External Control
- Cat 2 Hook Ends
- 4525kg Lift Capacity
- Swinging Drawbar - CAT A

WEIGHTS & DIMENSIONS

Wheelbase: **2400mm**

Length: **4268mm**

Total Height: **2494mm**

Total Weight: **4000kg**

DEALER DETAILS

DEUTZ-FAHR AGROFARM 5115 GS

40 KM/H

116HP



THE ALL-ROUNDER UTILITY TRACTOR.

Welcome to the world of the new Agrofarm 5-Series, an outstanding range of tractors that embody versatility, modularity, strength and an enviable good value for money ratio within the utility mid-segment.

The tractors in the Agrofarm 5-Series are designed to offer maximum flexibility while ensuring reliable and innovative performance. Agility is one of the distinctive features of these tractors, thanks to a remarkable steering angle and cutting-edge solutions such as the PowerShuttle with adjustable response, Stop & Go system, and Comfort Clutch, which ensure smooth and comfortable driving even in the most challenging situations.

ENGINE

- FARMotion LCR Diesel Engine
- 4 Cyl/3849cc Turbocharged Intercooled
- Liquid/Oil Cooled
- High-Pressure Diesel Injection/Common Rail
- Engine speed programming – 2 Settings
- 116Hp @ 2000 rpm (ECE R120)
- 6Hp Power Boost
- Torque 462 Nm @1600 rpm
- Powercore Air Filter with Dust Ejectors
- VISCO cooling fan
- Vertical exhaust pipe on cab
- 145 lt Fuel Capacity

TRANSMISSION

- 40/40 Forward/Reverse Gears
- Wet clutch Powershuttle
- Shuttle Modulation with 5 Settings
- 5 Speeds / 4 Ranges / 2 Stage Powershift
- 0.3Km/h – 40 ECO Km/h
- Comfort Clutch
- Front Wheel Assist - Push Button
- 4 Wheel Independent Braking
- 100% Front & Rear Diff Lock - Push Button
- 40 km/h Road Speed
- Pre-Arrangement For Front End Loader

PTO

- Independent Wet Multidisc Clutch
- 4 Speed PTO 540/540E – 1000/1000E
- 540 PTO @ 1958 Rpm 540E PTO @1641
- 1000 PTO @ 1960 Rpm 1000E PTO @ 1643
- 1" 3/8 - 6 Spline PTO Shaft

WHEEL EQUIPMENT & MISCELLANEOUS

- Adjustable Radial Wheel Equipment
- 480/70R24 Front 520/70R34 Rear
- Front Weight Frame
- Rear Wheel Ballast 172 kg
- Front Dynamic Fenders

OPERATOR ENVIRONMENT

- 4 Post Air Conditioned Cab
- High visibility transparent roof FOPS - compliant (polycarbonate hatch) with sunshade grid
- HYDRO Silent-Block Cab Suspension
- Ergonomic Controls
- Multi Function Digital Dash
- Deluxe Air Seat
- Passenger seat with seatbelt
- MP3 Radio Player with Twin Speakers
- Cup and smartphone holder
- Telescopic Mirrors
- 4 Rear & 4 Front Work Lights
- 2 Additional Front lights
- Rotating Beacon

HYD/LINKAGE/DRAWBAR

- Open Centre Hydraulic System
- 56 L/min Hyd Pump
- Separate 35L/min Steering Pump
- 2 Sets of Remotes - Kickout/Float
- Electronic Linkage c/w Position & Draft Controls
- Rear lift with External Control
- Cat 2 Hook Ends
- 5410kg Lift Capacity
- Swinging Drawbar - CAT A

WEIGHTS & DIMENSIONS

Wheelbase: **2400mm**

Length: **4268mm**

Total Height: **2796mm**

Total Weight: **4350kg**

DEALER DETAILS

DEUTZ-FAHR AGROFARM 5125 GS

40 KM/H

126HP



THE ALL-ROUNDER UTILITY TRACTOR.

Welcome to the world of the new Agrofarm 5-Series, an outstanding range of tractors that embody versatility, modularity, strength and an enviable good value for money ratio within the utility mid-segment.

The tractors in the Agrofarm 5-Series are designed to offer maximum flexibility while ensuring reliable and innovative performance. Agility is one of the distinctive features of these tractors, thanks to a remarkable steering angle and cutting-edge solutions such as the PowerShuttle with adjustable response, Stop & Go system, and Comfort Clutch, which ensure smooth and comfortable driving even in the most challenging situations.

ENGINE

- FARMotion LCR Diesel Engine
- 4 Cyl/3849cc Turbocharged Intercooled
- Liquid/Oil Cooled
- High-Pressure Diesel Injection/Common Rail
- Engine speed programming – 2 Settings
- 126Hp @ 2000 rpm (ECE R120)
- 6Hp Power Boost
- Torque 508 Nm @1600 rpm
- Powercore Air Filter with Dust Ejectors
- VISCO cooling fan
- Vertical exhaust pipe on cab
- 145 lt Fuel Capacity

TRANSMISSION

- 40/40 Forward/Reverse Gears
- Wet clutch Powershuttle
- Shuttle Modulation with 5 Settings
- 5 Speeds / 4 Ranges / 2 Stage Powershift
- 0.3Km/h – 40 ECO Km/h
- Comfort Clutch
- Front Wheel Assist - Push Button
- 4 Wheel Independent Braking
- 100% Front & Rear Diff Lock - Push Button
- 40 km/h Road Speed
- Pre-Arrangement For Front End Loader

PTO

- Independent Wet Multidisc Clutch
- 4 Speed PTO 540/540E – 1000/1000E
- 540 PTO @ 1958 Rpm 540E PTO @1641
- 1000 PTO @ 1960 Rpm 1000E PTO @ 1643
- Auto PTO
- PTO Switch on Rear Mudguards
- 1" 3/8 - 6 Spline PTO Shaft

WHEEL EQUIPMENT & MISCELLANEOUS

- Radial Wheel Equipment
- 440/65R28 Front 540/65R38 Rear
- Front Weight Frame
- Rear Wheel Ballast 240 kg
- Front Dynamic Fenders

OPERATOR ENVIRONMENT

- 4 Post Air Conditioned Cab
- High visibility transparent roof FOPS-compliant (polycarbonate hatch) with sunshade grid
- Hydro Silent Block Cab Suspension
- Ergonomic Controls
- Multi Function Digital Dash
- Deluxe Air Seat
- Passenger seat with seatbelt
- MP3 Radio Player with Twin Speakers
- Cup and smartphone holder
- Telescopic Mirrors
- 4 Rear & 4 Front Work Lights
- 2 Additional Front Lights
- Rotating Beacon

HYD/LINKAGE/DRAWBAR

- Open Centre Hydraulic System
- 56 L/min Hyd Pump
- Separate 35L/min Steering Pump
- 3 Sets of Remotes
 - Float & flow regulator on one
- Electronic Linkage c/w Position & Draft Controls
- Rear lift with electrohydraulic "EASY LIFT" system
- Cat 2 Hook Ends
- 5410kg Lift Capacity
- Swinging Drawbar - CAT A

WEIGHTS & DIMENSIONS

Wheelbase: **2400mm**

Length: **4268mm**

Total Height: **2808mm**

Total Weight: **4350kg**

DEALER DETAILS