

T25



Marshall
MACHINERY

Agricultural Sales and Services

Your Tasmanian TYM Dealers

A compact tractor engineered for productivity inside and out

The T25 tractor is proof that great things can indeed come in small packages. Offering enhanced power without sacrificing maneuverability, it's equipped with a powerful engine and ergonomic operator controls, ensuring both performance and comfort.




**2-range
hydrostatic
transmission
(HST)**



2 USB ports



**Wireless
smartphone
charger**



**3rd function
hydraulic valve**



Work lights



Toolbox



Superior operator features

Fully equipped with additional features to maximize operator comfort, this tractor is complete with auto throttle control, side by side HST pedals, a large cup holder, wireless smartphone charging dock and multiple USB ports to charge personal devices. These features are designed to promote productivity.



Auto throttle control

Auto throttle feature links the HST pedals to the engine throttle to synchronise the tractor's speed and engine RPM. This simplifies operation, helps increase productivity and reduces fuel consumption.



High torque, water-cooled Yanmar diesel engine

The Yanmar engine delivers more torque at lower RPMs than competitors in its class. This water-cooled engine heats up faster and stabilizes temperature effectively while the tractor is running. With Tier 4 certification, it meets stringent environmental and noise emission standards.



Upgraded detailing to reduce operator effort

Packed with value-added features to enhance ease of operation and reduce manual effort, including a brighter dash panel engineered to enhance operator awareness.



Turning Brakes

Equipped with reliable inboard wet disc brakes that provide consistent stopping power with minimal maintenance. Independent operation allows brake-assisted turning for smooth manoeuvring in tight areas or during loader work, giving greater control and agility on uneven terrain.



Comfortable and secure seating

In addition to a standard retractable seatbelt and cushioning, the seat is equipped with a heavy duty mechanical suspension. While the seat provides comfort, the suspension acts as a buffer on uneven ground, keeping the operator secure in situations where there is a risk of impact on the lower back. The seat can also be manually adjusted for weight, enabling operators to have the most optimal seating position.



TYM
TRACTORS

T25

HOW DO WE STACK UP?



— TYM WORLD - QUALITY. FEATURES. COMFORT. PERFORMANCE. —



AUTO THROTTLE CONTROL

Automatically increases engine RPM for more responsive performance.



928KG

TRACTOR WEIGHT

More weight means more driveline strength, traction, stability and pushing power.



695KG

LINKAGE LIFT CAPACITY

Lift heavier implements and tackle larger jobs with confidence.

300KG

LOADER RATED OPERATING LOAD

Move more material with every bucket load.

SPECIFICATIONS		TYM T25	KIOTI CS 2610	JD 1025R	KUBOTA BX2680
ENGINE	Horsepower	24.7	24.5	23.9	25.5
	@ Engine RPM	3000	3000	3200	3200
	Auto throttle control	YES	No	No	No
	Engine cubic capacity	1267	1007	1267	1001
	Push button cruise control	YES	Optional	Yes	Yes
TRANSMISSION - DRIVELINE	Turning brakes on left hand side	YES	No	No	No
	Side by side HST pedals	YES	Yes	Yes	No
	Maximum travel speed (km/h)	22	16	14.6	13.5
	23x8.5-12-12x16.5 industrial tyres standard with valve guarding	YES	No	No	No
	Tractor weight (Kg)	928	675	706	670
LINKAGE PTO & HYDRAULICS	Hydraulic system total flow (l/min)	27	24.6	24.5	23.5
	Hydraulic remotes	YES	Optional	Optional	Optional
	Linkage lift capacity (kg @ 610mm)	500	318	344	310
	External linkage stabiliser with adjustable lift arms	YES	No	Yes	No
	Wheelbase/width (mm)	1550/1342	1400/1188	1450/1202	1400/1145
DRIVER COMFORT & ERGONOMICS	True suspension seat with armrests	YES	No	No	No
	Wireless smartphone charging	YES	No	No	No
	Additional led adjustable spotlights	YES	No	No	No
	Toolbox	YES	No	No	No
	USB ports x 2	YES	No	No	No
FRONT END LOADER	Integrated loader joystick with dual open/close buttons, quick release bucket, euro-hitch and 4-in-1 bucket	YES	No	No	No
	Rated operating load (Kg)	300	175	-	180
AND THE WINNER IS...		21/22	2/22	4/22	2/22



30% HEAVIER

than the nearest competitor
928kg vs 706kg



**UP TO 60% MORE
LINKAGE LIFT CAPACITY**
500kg vs 310kg



**UP TO 70% HIGHER
LOADER RATED
OPERATING LOAD**
300kg vs 175kg



For more information
tym-tractors.com.au

Competitor Analysis E&OE
CCT25202608

Technical specifications

ENGINE	
Engine manufacturer	Yanmar 3TNV 80F
Type	Natural aspiration
Gross engine power	24.7 hp 18.4 kW
PTO power	18.3 hp 13.6 kW
Rated engine speed	3000 rpm
No. of cylinders	3
Displacement	77.3 cu. in. 1267 cc
Air cleaner	Single dry
Alternator	12V, 40A
Fuel system	IDI
POWERTRAIN	
Transmission type	HST
No. of speeds	Infinte 2-Range
Max. traveling speed	22 km/h
Brakes	Wet disc
Steering	Hydrostatic
Clutch	N/A
CAPACITIES	
Fuel tank	25 L
Coolant	3.6 L
Crankcase	2.7 L
Transmission/Hydraulics system	17 L
Front axle	4.5 L
PTO	
PTO type	Independent
PTO control	Electric/Hydro
PTO rear	540 rpm

HYDRAULIC SYSTEM	
Pump type	Single gear pump
Hydraulic flow	26.3 L/min
Category, 3-point hitch	I
Hitch lift capacity	703.6 kg
Hitch lift capacity at 24 inches behind link ends	557.8 kg
Lift control type	Position
No. of standard remote valves	1
DIMENSIONS & WEIGHTS	
Overall length with 3-point hitch	2610 mm
Overall width	1270 mm
Wheelbase	1550 mm
Height to top of ROPS	2320 mm
Min. ground clearance	260 mm
Min. turn radius with brakes	2390 mm
Min. turn radius without brakes	2840 mm
Weight with ROPS	928 kg
STANDARD TIRES	
R1 Agricultural - Front	6-12 4PR
R1 Agricultural - Rear	9.5-20 6PR
R3 Turf - Front	Turf Master 23x 8.50-12 NHS TL 4PR
R3 Turf - Rear	Multi-Trac CS 33x12.5-16.5 NHS TL 4PR
R4 Industrial - Front	23x8.50-14
R4 Industrial - Rear	36X12.5-15

The logo for Marshall Machinery, featuring a stylized orange 'M' above the word 'Marshall' in a large, bold, white sans-serif font, with the word 'MACHINERY' in a smaller, all-caps, white sans-serif font below it.

Agricultural Sales and Services

7 Legana Park Drive, Legana

03 6330 1808

www.marshallmachinery.com.au

sales@marshallmachinery.com.au